

Baylight® Prismatic Skylights

Provided by Behlen Building Systems



Good Iron. GREAT Experience!™

Baylight is

- Domed to pick up more of the sun's rays and allow more light to be transmitted into the building
- Curb mounted
- Prismatic feature to refract sunlight into micro beams directed into the building's interior
- Acrylic so it doesn't yellow like fiberglass
- Available in double glaze
- Thermal break tape standard between frame and curb
- Mill finish standard (aluminum)

Features

- Transmits 35% more light with superior light distribution
- Diffused 100% of the transmitted light
- Directs more of the transmitted light to the work plane
- Catches up to 20% more light at low sun angles
- 50% stronger than required by the Uniform Building Code
- Gives the quickest return on invested capital

Benefits

- Every Baylight will more than pay for itself through reduced electrical bills
- Adding Baylight to 3-4% of the roof area allows electric lights to be shut off approximately 2,000 hours per year for regular work schedules.
- This saves 30% of lamp and ballast maintenance costs

Considerations

- The advantage is not R-Value. The energy savings obtained by turning off the lights is greater than the heat or cooling use
- Daylighting rule of thumb is SFR (Skylight to Floor Ratio) should be approximately 3.5%
- Security screens are available

Daylighting Requirements

- Warehouse 0-30 ft. candles
- Manufacturing 30-50 ft. candles
- Office 50-70 ft. candles
- Retail 75-100 ft. candles

Builder Prices

- Baylight – Prismatic Triarch, Fixed Industrial Skylights and Curb Package
 - ✦ 4896 (4'X8') Double Glazed Acrylic Insulated Thermal Break Curb Seal Tape with Aluminum Curb \$1,320
 - ✦ Security Screen (4'X8') \$194
- Prepaid and additional freight charges are as follows:
 - ✦ Unit 1-5 \$300 per each
 - ✦ Unit 6+ \$100 add per each
 - ✦ Skylights are of 100% impact modified acrylic with prismatic glazings.
 - ✦ Double glazed skylight glazing are clear over white.
 - ✦ Roof support framing not included
 - ✦ Roof support framing must be added to building order
 - ✦ Maximum snow load 40 psf

BAYLIGHT FRAME DESIGN

**Baylight™
Prismatic
Skylights**

*Bay Insulation Systems
2929 Walker Drive
Green Bay, WI 54311
800.442.8464 Toll Free
www.bayinsulationsystems.com*

To order, contact your Behlen Building Systems representative.

AD-20125 4-13

