

26 GA - Siliconized Polyester Color Selection

STANDARD				
	POLAR WHITE SR .60 SRI 71	LIGHT STONE SR .50 SRI 57	ASH GRAY SR .47 SRI 55	SADDLE TAN SR .48 SRI 55
				
	BURNISHED SLATE SR .28 SRI 27	RUSTIC RED SR .36 SRI 38	IVY GREEN SR .28 SRI 27	CHARCOAL GRAY SR .27 SRI 26
PREMIUM*				
	HAWAIIAN BLUE SR .32 SRI 32	DESERT SAND SR .42 SRI 47	IVORY SR .65 SRI 78	GALVALUME
				
	EVERGREEN SR .34 SRI 35	BERRY SR .30 SRI 27	COCOA BROWN SR .28 SRI 27	CRIMSON RED SR .33 SRI 34
				
	BLACK SR .30 SRI 30	OLD TOWN GRAY SR .42 SRI 47	GALLERY BLUE SR .27 SRI 26	FERN GREEN SR .27 SRI 26
				
COLONY GREEN SR .31 SRI 32				

- **Solar Reflectivity (SR):** Solar reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance. ENERGY STAR requires an SR value of 0.25 or higher for steep slope roofing (above 2:12) and an SR value of 0.65 or higher for low slope roofing (2:12 or less). For more information, please visit www.energystar.gov.
- **Solar Reflectance Index (SRI):** The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing. For more information, visit www.usgbc.org.

All colors have a minimum quantity of 5,000 lbs.

* Selection of Premium Colors will require additional lead time and cost.