


(Southeast Sales and Manufacturing Region only)

### 24 Gauge - PVDF Color Selection



Custom colors and/or non-standard gauges will require prior approval.  
Minimum quantities, extended lead times and special pricing will also apply.

**Note:** Colors shown may vary in color or finish from actual panels.



Acrylic Galvalume®  
N/A

**Solar Reflectivity (SR):** Solar reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance.

ENERGY STAR requires an SR value of 0.25 or higher for steep slope roofing (above 2:12) and an SR value of 0.65 or higher for low slope roofing (2:12 or less). For more information, please visit [www.energystar.gov](http://www.energystar.gov).

**Solar Reflectance Index (SRI):** The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing. For more information, visit [usgbc.org](http://usgbc.org).

### Color Availability

Colors	24 Gauge PBR, Rev-PBR, SurLok
Acrylic Galvalume®	✓
Regal White	✓
Snow White	✓
Almond	✓
Sandstone	✓
Ash Gray	✓
Pre-Weathered Galvalume®	✓
Dark Charcoal	✓
Brownstone	✓
Medium Bronze	✓
Colonial Red	✓
Regal Blue	✓
Classic Green	✓

### Panel Profiles

