


(Southeast Sales and Manufacturing Region only)

2812 Tallevast Road
Sarasota, Florida 34243

Phone: 941-755-7073
Fax: 941-755-3067
www.behlenbuildingsystems.com

26 Gauge - Siliconized Polyester Color Selection



Polar White
SR .64 SRI 77



Light Stone
SR .56 SRI 65



Ash Gray
SR .46 SRI 52



Saddle Tan
SR .47 SRI 53



Burnished Slate
SR .34 SRI 35



Rustic Red
SR .36 SRI 38



Ivy Green
SR .28 SRI 27



Charcoal Gray
SR .37 SRI 31




Hawaiian Blue
SR .31 SRI 31



Desert Sand
SR .42 SRI 47



Ivory
SR .69 SRI 84



Acrylic Galvalume®
N/A

Custom colors and/or non-standard gauges will require prior approval. Minimum quantities, extended lead times and special pricing will also apply.

Note: Colors shown may vary in color or finish from actual panels.

Solar Reflectivity (SR): Solar reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance.

ENERGY STAR requires an SR value of 0.25 or higher for steep slope roofing (above 2:12) and an SR value of 0.65 or higher for low slope roofing (2:12 or less). For more information, please visit www.energystar.gov.

Solar Reflectance Index (SRI): The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing. For more information, visit usgbc.org.

Color Availability

Colors	26 Gauge PBR
Polar White	✓
Light Stone	✓
Ash Gray	✓
Saddle Tan	✓
Burnished Slate	✓
Rustic Red	✓
Ivy Green	✓
Charcoal Gray	✓
Hawaiian Blue	✓
Desert Sand	✓
Ivory	✓
Acrylic Galvalume®	✓

Panel Profile

